


Flexible Connectors • Çelik Spiral Rakorları

Straight - Squeeze Type - Zinc Die Cast • Düz - Sıkmalı Tip - Zamak



E358461
(All Sizes except 3 1/2")
(3 1/2" - E358457)

Features

- Squeeze type straight
- Available with insulated throat

Applications

- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- The 3/8" can also be used with steel and aluminum MC cable

- 3/8" size fits 1/2" knockout
- Suitable for: 3/8" steel flexible conduit, #14/2 metal conduit and #4-2 wire steel armored cable, 3/4" steel flexible metal conduit and #6-3 wire steel armored cable, 1" steel and reduced wall steel flexible metal conduit and #2-2 wire steel armored cable and 1-1/4" - 4" steel flexible metal conduit


Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)			Screws
					A	B (Min.-Max.)	C	
E-L 42	3/8" (1/2" KO)	50	500	35	1.00	0.58-0.61	.370	1
E-L 42-1	1/2"	25	250	25	1.47	0.74-0.95	.400	1
E-L 42-2	3/4"	25	250	32	1.58	0.88-1.11	.400	1
E-L 42-3	1"	10	100	20	1.75	1.14-1.38	.540	1
E-L 42-4	1-1/4"	10	100	29	1.91	1.42-1.65	.640	1
E-L 42-5	1-1/2"	5	50	20	2.09	1.68-1.94	.750	1
E-L 42-6	2"	10	40	21	2.34	2.08-2.56	.740	1
E-L 42-7	2-1/2"	—	10	9	2.81	2.85-3.25	.875	2
E-L 42-8	3"	—	10	17	3.84	3.33-3.63	1.03	2
E-L 42-9	3-1/2"	—	1	3	4.19	3.75-4.10	1.03	2
E-L 42-10	4"	—	1	3	4.56	4.18-4.58	1.03	2

* Insulated models are also available. Please add "-A" to the part number while ordering (E-L 42-A, E-L 42-1-A, etc...)

90° - Squeeze Type - Zinc • 90° - Sıkmalı Tip - Zamak



E358461
(All Sizes except 3 1/2")
(3 1/2" - E358457)

Features

- Squeeze type

Applications

- Indoor use only
- In a dry location, use to connect flexible metal conduit, aluminum and steel AC and MC cable to a steel outlet box or other metal enclosure

- 3/8" size fits 1/2" knockout
- Suitable For: 3/8" - 3/4" steel and aluminum armored cable, steel and aluminum interlocked metal clad cable, flexible cord, and 1" - 4" flexible metal conduit

Standard Material


- Zinc die cast
- Zinc plated steel strap

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case	Dimensions (in)			Screws
					A	B (Min.-Max.)	C	
E-L 110	3/8" (1/2" KO)	50	500	45	1.740	0.43-0.72	.370	2
E-L 110-1	1/2"	25	250	35	2.110	0.64-1.03	.400	2
E-L 110-2	3/4"	10	100	20	2.400	0.76-1.15	.400	2
E-L 110-3	1"	5	50	19	2.870	1.09-1.73	.540	2
E-L 110-4	1-1/4"	10	40	20	4.000	1.34-1.97	.640	2
E-L 110-5	1-1/2"	---	5	5	6.000	1.65-2.61	.750	2
E-L 110-6	2"	---	5	6	6.000	1.54-2.54	.740	2
E-L 110-7	2-1/2"	---	5	18	7.187	2.45-2.98	.875	4
E-L 110-8	3"	---	2	9	7.875	2.93-3.45	1.031	4
E-L 110-9	3-1/2"	---	1	9	9.400	3.28-3.95	1.031	4
E-L 110-10	4"	---	1	10	10.200	3.68-4.43	1.031	4

* Insulated models are also available. Please add "-A" to the part number while ordering (E-L 110-A, E-L 110-1-A, etc...)

* İzoleli tip rakorları sipariş etmek için katalog kodunun sonuna "A" ekleyiniz: 110A, 110-1-A gibi.

Screw In Type - Zinc Die Cast • İçten Geçmeli Tip - Zamak



Features

- Screw in type

Applications

- Indoor use only
- Use to connect flexible metallic conduit to steel outlet box, load center or other metal enclosure
- 3/8" size fits 1/2" knockout
- 1-1/2" - steel and steel reduced wall flexible metal conduit


Standard Material

- Zinc die cast

Catalog Number	Size	KO	Unit Carton	Ship Case	Weight / Case	Dimensions (in)	
						A	B
E-L 44	3/8"	1/2"	50	500	30	1.31	.92
E-L 44-1	1/2"	1/2"	50	500	30	1.38	.92
E-L 44-2	3/4"	3/4"	25	250	25	1.63	1.10
E-L 44-3	1"	1"	25	250	40	1.94	1.38
E-L 44-4	1-1/4"	1-1/4"	10	100	28	2.12	1.75
E-L 44-5	1-1/2"	1-1/2"	10	40	15	2.31	2.13
E-L 44-6	2"	2"	10	40	25	2.58	2.67

Flex Couplings • Çelik Spiral Mufları

Screw In Type - Zinc Die Cast • İçten Geçmeli Tip - Zamak



Features

- Screw in coupling

Applications

- Indoor use only
- Use to join two pieces of flexible metallic conduit


Standard Material

- Zinc die cast

Catalog Number	Conduit Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
E-L 45-1	1/2"	50	500	30	1.80	.92	1.062
E-L 45-2	3/4"	25	250	23	2.09	1.12	1.372
E-L 45-3	1"	25	250	38	2.41	1.37	1.687
E-L 45-4	1-1/4"	10	100	25	2.74	1.81	2.125
E-L 45-5	1-1/2"	10	40	16	3.05	2.12	2.375
E-L 45-6	2"	10	40	24	3.27	2.67	2.937

Combination Couplings • Ara Bağlantı Parçası

Set Screw Type - EMT to Flex • Vidalı Tip - EMT / Spiral Bağlantı Parçası



Features

- Set screw type
- EMT to flex combination coupling
- UL listed

Applications

- Indoor use only
- Use to join EMT conduit to flexible metal conduit

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A Min.	A Max.	B
E-L 153	1/2" - 3/8"	25	250	25	.17	.63	1.35
E-L 153-1	1/2" - 1/2"	25	250	25	.75	.95	1.65
E-L 153-2	3/4" - 3/4"	—	100	15	.75	1.20	1.93
E-L 153-3	1" - 1"	—	50	13	1.14	1.61	2.12

Anti Short Bushings • Çelik Spiral Entülleri



Catalog Number	Size	Flex Size	Per Bag
E-AS-0-PL	0	5/8"	100
E-AS-1-PL	1	3/8"	100
E-AS-2-PL	2	7/16"	50
E-AS-3-PL	3	1/2"	50
E-AS-4-PL	4	3/4"	50
E-AS-5-PL	5	1"	25
E-AS-6-PL	6	1 1/4"	10
E-AS-7-PL	7	1 1/2"	10
E-AS-8-PL	8	2 to 2 1/2"	10

Features

- Sold in bulk or bags
- With pull tab

Applications

- Indoor use only
- Insert one bushing at each end of conduit to protect wire

Standard Material

- Polyethylene

Bushings are packed in clear poly bags
Anti-short bushings have a temperature rating of 90°C