

PRODUCT INTRODUCTION

The rigid conduit coupling is used to connect the electrical steel conduits together, thus extending the length of the conduit pipe. It is manufactured from seamless steel pipes according to ANSI C80.1 and UL6 standards with UL certificate number of E468594 .Its trade size can be from 1/2" to 6" . Electroline produces the rigid conduit coupling zinc plate on both outer side and inner side. The internal surface can also be electro-galvanized completely.

DIMENSION AND PACKING CHART

Trade Size	Weight Per 100 pcs		Outside Diameter		Minimum Acceptable Length		Standard Carton Qty PCS	Weight Per Carton	
	KG	LBS	mm	in.	mm	in.		KG	LBS
1/2"	6.35	14	25.7	1.012	41.3	1.626	400	25.4	56
3/4"	9.07	20	31.8	1.252	41.7	1.642	300	27.2	60
1"	14.06	31	38.7	1.524	50.0	1.969	180	25.3	56
1-1/4"	17.69	39	47.5	1.870	51.6	2.031	100	17.7	39
1-1/2"	25.4	56	54.7	2.154	52.4	2.063	75	19.1	42
2"	33.11	73	67.3	2.650	54.0	2.126	60	19.9	44
2-1/2"	83.92	185	82.6	3.252	81.0	3.189	12	10.1	22
3"	102.51	226	98.3	3.870	84.1	3.311	8	8.2	18
3-1/2"	162.39	358	114.3	4.500	86.5	3.406	4	6.5	14
4"	181.44	400	123.8	4.874	89.3	3.516	4	7.3	16
5"	225.44	497	152.4	6.000	100.4	3.953	2	4.5	10
6"	370.10	816	182.9	7.201	108.0	4.252	3	11.1	24



Certificate No: E468594 (20140519)

