

FLEXIBLE STEEL CONDUIT – COMMERCIAL GRADE

- Square locked
- Made from galvanized sheet steel
- High flexibility
- Low fire hazard
- High abrasion resistant
- Suitable for general building, high rises, factory, underfloor wiring in office blocks
- High mechanical strength



Catalog Number	TRADE Size (inch)	Inside Diameter		Outside Diameter		Roll Length (m)
		Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	
E-STL-N-050	½	12.20	12.80	15.00	15.80	50
E-STL-N-075	¾	18.60	19.50	21.50	22.50	50
E-STL-N-100	1	24.60	25.60	28.00	28.80	30
E-STL-N-125	1-¼	31.50	32.30	36.60	38.00	15
E-STL-N-150	1-½	37.80	38.50	41.60	43.00	15
E-STL-N-200	2	49.80	50.60	55.20	56.20	15
E-STL-N-250	2-½	62.50	63.50	69.40	70.80	10
E-STL-N-300	3	75.50	76.50	82.50	83.80	10
E-STL-N-400	4	101.50	102.20	108.00	109.10	10

FLEXIBLE STEEL CONDUIT – INDUSTRIAL GRADE

- Interlocked
- Made from hot-dip galvanized steel, special thickness
- High flexibility
- Low fire hazard High abrasion resistant
- Suitable for general building, high rises, factory, underfloor wiring in office blocks
- High mechanical strength



Catalog Number	Trade Size (inch)	Inside Diameter		Outside Diameter		Roll Length (m)
		Min. (mm)	Max. (mm)	Min. (mm)	Max. (mm)	
E-STL-H-050	½	15.80	16.50	18.20	18.90	50
E-STL-H-075	¾	20.70	21.60	23.20	23.90	50
E-STL-H-100	1	26.00	27.00	29.20	30.00	30
E-STL-H-125	1-¼	35.00	35.80	38.30	39.00	15
E-STL-H-150	1-½	40.20	41.00	43.30	44.20	15
E-STL-H-200	2	51.00	51.80	54.20	56.00	15
E-STL-H-250	2-½	62.80	64.20	67.50	68.60	10
E-STL-H-300	3	77.80	79.00	82.80	84.00	10
E-STL-H-400	4	101.20	102.80	106.00	107.60	10