


# ELBOWS, COUPLINGS AND NIPPLES

## EMT Elbows

### 90° - Galvanized Steel



E528770  
UL 797 and ANSI C80.3  
Federal Specification WW-C-563



#### Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

#### Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit

#### Standard Material

- Galvanized steel


Catalog Number	Size	Ship Case	Weight/ Case lbs	(A) Min. UL Radius	(B) Straight Leg Each End	(C) Offset
E-TTE 1/2	1/2"	50	12	4.000	2.875	6.343
E-TTE 3/4	3/4"	50	22	4.500	2.875	6.781
E-TTE 1	1"	20	16	5.750	3.00	8.901
E-TTE 1 1/4	1-1/4"	20	29	7.250	3.25	10.25
E-TTE 1 1/2	1-1/2"	10	20	8.250	3.625	11.937
E-TTE 2	2"	10	27	9.500	4.1875	14.031
E-TTE 2 1/2	2-1/2"	50	230	10.500	5.25	16.00
E-TTE 3	3"	35	240	13.000	5.8125	18.947
E-TTE 3 1/2	3-1/2"	35	360	15.000	6.75	22.218
E-TTE 4	4"	25	310	16.000	6.9375	23.437

## EMT Elbows

### 45° - Galvanized Steel



E528770  
UL 797 and ANSI C80.3  
Federal Specification WW-C-563



#### Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

#### Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit

#### Standard Material

- Galvanized steel

Catalog Number	Size	Ship Case	Weight/ Case lbs	(A) Min. UL Radius	(B) Straight Leg Each End
E-TTE 1/2 X 45	1/2"	50	11	4.00	2.875
E-TTE 3/4 X 45	3/4"	50	19	4.50	2.875
E-TTE 1 X 45	1"	35	25	5.750	3.00
E-TTE 1 1/4 X 45	1-1/4"	30	30	7.250	3.25
E-TTE 1 1/2 X 45	1-1/2"	15	44	8.250	3.625
E-TTE 2 X 45	2"	15	31	9.5	4.1875
E-TTE 2 1/2 X 45	2-1/2"	1	3	10.5	5.25
E-TTE 3 X 45	3"	1	5	13	5.8125
E-TTE 3 1/2 X 45	3-1/2"	1	7.5	15	6.75
E-TTE 4 X 45	4"	1	9	16	6.9375