

ELECTROTITE® LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT – INTERLOCKED

- Galvanized steel core for lasting mechanical protection
- Excellent protection against impact, moisture, vapor and abrasion
- Bendable and high flexibility
- Coated with high grade PVC
- Suitable for industrial, commercial and residential applications
- Can be used both indoor and outdoor
- Easily cut to length on the job
- Accepts standard UL Listed liquid-tight connectors



Catalog Number	Size (inch)	Inside Diameter				Outside Diameter				Bending Radius		Roll Length (ft)
		Min. (inch)	Max. (mm)	Min. (inch)	Max. (mm)	Min. (inch)	Max. (mm)	Min. (inch)	Max. (mm)			
E-EF-050	½	0.622	15.80	0.642	16.31	0.820	20.83	0.840	21.34	2	50	100
E-EF-075	¾	0.820	20.83	0.840	21.34	1.030	26.16	1.050	26.67	2-¾	65	100
E-EF-100	1	1.041	26.44	1.066	27.08	1.290	32.77	1.315	33.40	5	125	50
E-EF-125	1-¼	1.380	35.05	1.410	35.81	1.630	41.40	1.660	42.16	6	150	50
E-EF-150	1-½	1.575	40.00	1.600	40.64	1.865	47.37	1.900	48.26	7	175	25
E-EF-200	2	2.020	51.31	2.045	51.94	2.340	59.44	2.375	60.33	9	225	25
E-EF-250	2-½	2.480	62.99	2.505	63.63	2.840	72.14	2.875	73.03	11	275	25
E-EF-300	3	3.070	77.98	3.100	78.74	3.460	87.88	3.500	88.90	15-½	390	25
E-EF-350	3-½	3.500	88.90	3.540	89.92	3.960	100.58	4.000	101.60	18	450	25
E-EF-400	4	4.000	101.60	4.040	102.62	4.460	113.28	4.500	114.30	22	550	25

HALOGEN FREE LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT EFF – LSZH (LOW SMOKE ZERO HALOGEN)

- Interlocked steel construction
- Hot dip galvanized steel core
- Low smoke, Non-toxic, None-halogen
- Coated with white PE
- Flame retardant
- UV resistant
- Accepts standard UL Listed liquid-tight connectors
- Suitable for schools, hospitals, airports, high rise buildings or underground tunnels
- Suitable for concrete embedment and direct burial



Catalog Number	Trade Size (Inch)	Inside Diameter (mm)		Outside Diameter (mm)		Bending Radius (mm)	Roll Length (mt)
		Min.	Max.	Min.	Max.		
E-EFF-050	½	15.70	16.3000	20.2000	20.7000	65	30
E-EFF-075	¾	20.70	21.2000	25.5000	26.1000	75	30
E-EFF-100	1	26.00	26.6000	31.6000	32.2000	100	30
E-EFF-125	1-¼	34.70	35.4000	40.8000	41.5000	125	15
E-EFF-150	1-½	40.00	40.6000	46.6000	47.2000	150	15
E-EFF-200	2	51.30	51.9000	58.1000	58.7000	175	15
E-EFF-250	2-½	62.90	63.3000	72.1000	73.0000	200	10
E-EFF-300	3	77.90	78.7000	87.9000	88.9000	225	10