

LIQUIDTIGHT FLEXIBLE STEEL CONDUIT – UL LISTED

- Galvanized steel core for lasting mechanical protection
- Durable, abrasion-resistant PVC jacket won't wrinkle or shrink from cut ends
- Smooth interior for easy wire pull-through
- Complete protection against most liquids and moisture vapor
- Resists sunlight, heat, oil, and chemical degradation; Rated: -20 deg. C to +60 deg. C
- Superior protection for circuits located in hostile environments
- Complies with UL standard 360 under UL File # E530072
- Copper bond wire in 3/8" - 1 1/4"
- RoHS WEEE compliant
- Approved for direct burial and in concrete



E530772

| Catalog Number | Size (inch) | Inside Diameter | | | | Outside Diameter | | | | Bending Radius | | Roll Length (ft) |
|----------------|-------------|-----------------|-----------|-------------|-----------|------------------|-----------|-------------|-----------|----------------|-----|------------------|
| | | Min. (inch) | Max. (mm) | Min. (inch) | Max. (mm) | Min. (inch) | Max. (mm) | Min. (inch) | Max. (mm) | | | |
| E-EF-050-UL | 1/2 | 0.622 | 15.80 | 0.642 | 16.31 | 0.820 | 20.83 | 0.840 | 21.34 | 3-1/4 | 80 | 100 |
| E-EF-075-UL | 3/4 | 0.820 | 20.83 | 0.840 | 21.34 | 1.030 | 26.16 | 1.050 | 26.67 | 4-1/4 | 105 | 100 |
| E-EF-100-UL | 1 | 1.041 | 26.44 | 1.066 | 27.08 | 1.290 | 32.77 | 1.315 | 33.40 | 7-1/2 | 190 | 50 |
| E-EF-125-UL | 1-1/4 | 1.380 | 35.05 | 1.410 | 35.81 | 1.630 | 41.40 | 1.660 | 42.16 | 8 | 200 | 50 |
| E-EF-150-UL | 1-1/2 | 1.575 | 40.00 | 1.600 | 40.64 | 1.865 | 47.37 | 1.900 | 48.26 | 9 | 225 | 25 |
| E-EF-200-UL | 2 | 2.020 | 51.31 | 2.045 | 51.94 | 2.340 | 59.44 | 2.375 | 60.33 | 11 | 275 | 25 |
| E-EF-250-UL | 2-1/2 | 2.480 | 62.99 | 2.505 | 63.63 | 2.840 | 72.14 | 2.875 | 73.03 | 14 | 350 | 25 |
| E-EF-300-UL | 3 | 3.070 | 77.98 | 3.100 | 78.74 | 3.460 | 87.88 | 3.500 | 88.90 | 17-1/2 | 440 | 25 |
| E-EF-350-UL | 3-1/2 | 3.500 | 88.90 | 3.540 | 89.92 | 3.960 | 100.58 | 4.000 | 101.60 | 20 | 500 | 25 |
| E-EF-400-UL | 4 | 4.000 | 101.60 | 4.040 | 102.62 | 4.460 | 113.28 | 4.500 | 114.30 | 24 | 600 | 25 |

