


EMT Straps

Snap-On Type - One Hole - Steel



E528774

Features

- Snap-on type EMT strap with one hole
- Inverted rib for strength

Applications

- Support EMT conduit

Standard Material

- Steel


Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case lbs	Dimensions (in)	
					A	B
E-L 650	½"	100	1000	25	1.79	.57
E-L 651	¾"	100	1000	30	1.96	.62
E-L 652	1"	50	500	25	2.25	.75
E-L 653	1-¼"	25	250	20	2.85	.88
E-L 654	1-½"	10	100	12	3.16	.99
E-L 655	2"	10	100	16	3.93	1.10
E-L 606T*	2-½"	—	50	21	5.00	1.28
E-L 607T*	3"	—	25	13	5.55	1.28
E-L 608T*	3-½"	—	25	18	6.37	1.28
E-L 609T*	4"	---	25	20	6.87	1.28
E-L 610T*	5"	---	10	5	9.00	1.50
E-L 611T*	6"	---	10	6	10.35	1.50

* EMT and Rigid

Snap-On Type - Two Hole - Steel



E528774

Features

- Snap-on type EMT strap with two holes

Applications

- Use to support EMT conduit where greater load bearing is required

Standard Material

- Steel

Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/ Case lbs	Dimensions (in)	
					A	B
E-L 660-1	½"	50	500	10	2.20	.56
E-L 660-2	¾"	50	500	10	2.67	.62
E-L 660-3	1"	50	500	15	2.97	.68
E-L 660-4	1-¼"	20	200	12	3.67	.75
E-L 660-5	1-½"	20	200	16	4.22	.88
E-L 660-6	2"	—	50	7	4.91	1.00
E-L 660-7*	2-½"	—	25	6	5.91	1.00
E-L 660-8*	3"	—	25	7	6.71	1.00
E-L 660-9*	3-½"	—	25	8	7.51	1.00
E-L 660-10*	4"	—	25	7	8.31	1.00
E-L 660-11*	5"	—	10	5	10.60	1.25
E-L 660-12*	6"	—	10	6	11.85	1.28

* EMT and Rigid