


EMT Connectors and Couplings

Compression Type Connector - Steel



E528774
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1

Features

- Compression type connector and couplings
- Concrete tight
- Assembled with a steel locknut
- Available with insulated throat

Applications

- Connectors: Use to join EMT to box or enclosure
- Couplings: Use to join two lengths of EMT

Standard Material

- Steel

Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case lbs	Dimensions (in)		
					A	B	C
E-L 21 ST	½"	25	250	30	1.750	1.250	.406
E-L 23 ST	¾"	25	250	43	1.813	1.563	.406
E-L 25 ST	1"	10	100	25	2.000	1.813	.406
E-L 27 ST	1-¼"	---	25	12	2.750	2.188	.500
E-L 29 ST	1-½"	---	20	12	3.000	2.438	.500
E-L 31 ST	2"	---	15	15	3.188	2.938	.688
E-L 33 ST	2-½"	---	12	19	3.875	3.688	.750
E-L 35 ST	3"	---	6	15	4.375	4.313	.938
E-L 37 ST	3-½"	---	6	16	4.500	4.875	.938
E-L 39 ST	4"	---	6	21	4.750	5.375	.938


Compression Type Connector with Insulated Throat - Steel



E528774
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case lbs	Dimensions (in)		
					A	B	C
E-L 21 ST-A	½"	25	250	30	1.750	1.250	.406
E-L 23 ST-A	¾"	25	250	33	1.813	1.563	.406
E-L 25 ST-A	1"	10	100	28	2.000	1.813	.406
E-L 27 ST-A	1-¼"	---	25	8	2.750	2.188	.500
E-L 29 ST-A	1-½"	---	20	9	3.000	2.438	.500
E-L 31 ST-A	2"	---	15	12	3.188	2.938	.688
E-L 33 ST-A	2-½"	---	12	19	3.875	3.688	.750
E-L 35 ST-A	3"	---	12	25	4.375	4.313	.938
E-L 37 ST-A	3-½"	---	6	15	4.500	4.875	.938
E-L 39 ST-A	4"	---	6	19	4.750	5.375	.938

Compression Type Coupling - Steel



E528774
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB 1

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case lbs	Dimensions (in)	
					A	B
E-L 22 ST	½"	25	250	32	1.688	1.250
E-L 24 ST	¾"	25	250	40	2.000	1.563
E-L 26 ST	1"	10	100	31	2.125	1.813
E-L 28 ST	1-¼"	---	25	15	3.063	2.188
E-L 30 ST	1-½"	---	20	15	3.125	2.438
E-L 32 ST	2"	---	15	18	3.375	2.938
E-L 34 ST	2-½"	---	6	14	4.875	3.688
E-L 36 ST	3"	---	6	19	5.250	4.313
E-L 38 ST	3-½"	---	6	21	5.500	4.875
E-L 40 ST	4"	---	3	15	5.750	5.375