

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Grounding and Bonding Equipment

COMPANY

Electroline Manufacturing LLC

515 E Las Olas Blvd, Suite 120

Fort Lauderdale, FL 33301 United States

E528776



Trademark and/or Tradename: "ELECTROLINE",

Note: For additional marking information, refer to the [Guide Information Page](#)

View model for additional information

Conduit Grounding Bushings-Insulated, Model(s): [RGB100M](#), [RGB100SS](#), [RGB125M](#), [RGB150M](#), [RGB15M](#), [RGB15SS](#), [RGB20M](#), [RGB20SS](#), [RGB25M](#), [RGB25SS](#), [RGB32M](#), [RGB32SS](#), [RGB40M](#), [RGB40SS](#), [RGB50M](#), [RGB50SS](#), [RGB65M](#), [RGB65SS](#), [RGB80M](#), [RGB80SS](#), [RGB90M](#), [RGB90SS](#)

Conduit Grounding Bushings-Insulated-PVC COATED, Model(s): [RGB100P](#), [RGB125P](#), [RGB150P](#), [RGB15P](#), [RGB20P](#), [RGB25P](#), [RGB32P](#), [RGB40P](#), [RGB50P](#), [RGB65P](#), [RGB80P](#), [RGB90P](#)

Grounding Liquid-tight Connectors-45 Degree Insulated, Model(s): [LTGC45100SS](#), [LTGC4515SS](#), [LTGC4525SS](#), [LTGC4532SS](#), [LTGC4540SS](#), [LTGC4550SS](#), [LTGC4565SS](#), [LTGC4580SS](#), [LTGC4590SS](#)

Grounding Liquid-tight Connectors-90 Degree Insulated, Model(s): [LTGC90100SS](#), [LTGC9015SS](#), [LTGC9020SS](#), [LTGC9025SS](#), [LTGC9032SS](#), [LTGC9040SS](#), [LTGC9050SS](#), [LTGC9065SS](#), [LTGC9080SS](#), [LTGC9090SS](#)

Grounding Liquid-tight Connectors-Straight Insulated, Model(s): [LTGC00100SS](#), [LTGC0015SS](#), [LTGC0025SS](#), [LTGC0032SS](#), [LTGC0040SS](#), [LTGC0050SS](#), [LTGC0065SS](#), [LTGC0080SS](#), [LTGC0090SS](#)

Grounding lugs, Model(s): [1/0-8AL](#), [3/0-6AL](#), [4-14AL](#)

Liquid-tight Connectors with grounding lugs-45 Degree Insulated, Model(s): [LTGC4510](#), [LTGC45100](#), [LTGC4515](#), [LTGC4520](#), [LTGC4525](#), [LTGC4532](#), [LTGC4540](#), [LTGC4550](#), [LTGC4565](#), [LTGC4580](#), [LTGC4590](#)

Liquid-tight Connectors with grounding lugs-45 Degree Insulated-PVC COATED, Model(s): [LTGC45100P](#), [LTGC4510P](#), [LTGC4515P](#), [LTGC4520P](#), [LTGC4525P](#), [LTGC4532P](#), [LTGC4540P](#), [LTGC4565P](#), [LTGC4580P](#), [LTGC4590P](#)

Liquid-tight Connectors with grounding lugs-90 Degree Insulated, Model(s): [LTGC9010](#), [LTGC90100](#), [LTGC9015](#), [LTGC9020](#), [LTGC9025](#), [LTGC9032](#), [LTGC9040](#), [LTGC9050](#), [LTGC9065](#), [LTGC9080](#), [LTGC9090](#)

Liquid-tight Connectors with grounding lugs-90 Degree Insulated-PVC COATED, Model(s): [LTGC90100P](#), [LTGC9010P](#), [LTGC9015P](#), [LTGC9020P](#), [LTGC9025P](#), [LTGC9032P](#), [LTGC9040P](#), [LTGC9050P](#), [LTGC9065P](#), [LTGC9080P](#), [LTGC9090P](#)

Liquid-tight Connectors with grounding lugs-Straight Insulated, Model(s): [LTGC0010](#), [LTGC00100](#), [LTGC0015](#), [LTGC0020](#), [LTGC0025](#), [LTGC0032](#), [LTGC0040](#), [LTGC0050](#), [LTGC0065](#), [LTGC0090](#)

Liquid-tight Connectors with grounding lugs-Straight Insulated-PVC COATED, Model(s): [LTGC00100P](#), [LTGC0010P](#), [LTGC0015P](#), [LTGC0020P](#), [LTGC0025P](#), [LTGC0032P](#), [LTGC0040P](#), [LTGC0050P](#), [LTGC0065P](#), [LTGC0080P](#), [LTGC0090P](#)

Watertight Conduit Grounding Hubs-Insulated, Model(s): [STG100](#), [STG100M](#), [STG100SS](#), [STG15](#), [STG15M](#), [STG15SS](#), [STG20](#), [STG20M](#), [STG20SS](#), [STG25](#), [STG25M](#), [STG25SS](#), [STG32](#), [STG32M](#), [STG32SS](#), [STG40](#), [STG40M](#), [STG40SS](#), [STG50](#), [STG50M](#), [STG50SS](#), [STG65](#), [STG65M](#), [STG65SS](#), [STG80](#), [STG80M](#), [STG80SS](#), [STG90](#), [STG90M](#), [STG90SS](#)

Watertight Conduit Grounding Hubs-Insulated-PVC COATED, Model(s): [STG100P](#), [STG15P](#), [STG20P](#), [STG25P](#), [STG32P](#), [STG40P](#), [STG50P](#), [STG65P](#), [STG80P](#), [STG90P](#)

Zinc insulated ground bushings - lay-in lug, Model(s): [E-L 52 IMGL](#), [E-L 60 IMGL](#), [E-L 61 IMGL](#), [E-L 65 IMGL](#), [E-L 69 IMGL](#), [E-L 75 IMGL](#), [E-L 76 IMGL](#), [E-L 90 IMGL](#), [E-L 91 IMGL](#), [E-L 92 IMGL](#)

[Last Updated](#) on 2025-11-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."